

**PRODUCT SPECIFICATIONS**

Elkay SwirlFlo<sup>®</sup> Bi-level ADA Fountain Filtered Refrigerated Stainless. Chilling Capacity of 8.0 GPH (gallons per hour) of 50° F drinking water, based on 80° F inlet water and 90° F ambient, per ASHRAE 18 testing. Features shall include Filtered. Furnished with Flexi-Guard<sup>®</sup> Safety Bubbler. Mechanical Front Bubbler Button activation. Product shall be Wall Mount (Inwall Frame/Plate), for Indoor applications, serving 2 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120.



|                                 |                                         |
|---------------------------------|-----------------------------------------|
| <b>Special Features:</b>        | Filtered                                |
| <b>Finish:</b>                  | Stainless Steel                         |
| <b>Power:</b>                   | 115V/60Hz                               |
| <b>Bubbler Style:</b>           | Flexi-Guard <sup>®</sup> Safety Bubbler |
| <b>Activation by:</b>           | Mechanical Front Bubbler Button         |
| <b>Mounting Type:</b>           | Wall Mount (Inwall Frame/Plate)         |
| <b>Chilling Capacity*:</b>      | 8.0 GPH                                 |
| <b>Rated Watts:</b>             | 370                                     |
| <b>Dimensions (L x W x H):</b>  | 38-1/2" x 19" x 40-13/16"               |
| <b>Approx. Shipping Weight:</b> | 108 lbs.                                |
| <b>Installation Location:</b>   | Indoor                                  |
| <b>No. of Stations Served:</b>  | 2                                       |

\*Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled drinking water.

**Special Note: Requires mounting frame MF200 which can be ordered seperately for early installation.**

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Filter is certified to NSF 42 and 53 for lead, cyst, particulate, chlorine, taste and odor reduction. 1,500 gal. capacity.

**COOLING SYSTEM**

- Compressor: Hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled, copper tube with aluminum fins. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with is fully insulated with EPS foam that meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R-134a is controlled by accurately calibrated capillary tube.
- Temperature Control: Easily accessible enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements.

**Included with Product:** Fountain, Filter, Chiller

**▼ Ships in multiple boxes.**

A Century of Tradition and Quality. For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



**PRODUCT COMPLIANCE**

- ADA & ICC A117.1
- ASME A112.19.3/CSA B45.4
- CAN/CSA C22.2 No. 120
- NSF/ANSI 42, 53, 61 (Q≤1), & 372 (lead free)
- UL 399



Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

- [Installation Instructions \(PDF\) - 1000003097](#)
- [Installation Instructions \(PDF\) - 97924C](#)

**5 Year Limited Warranty** on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. **Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.**

[Warranty \(PDF\)](#)

PART: \_\_\_\_\_ QTY: \_\_\_\_\_

PROJECT: \_\_\_\_\_





CONTACT: \_\_\_\_\_

DATE: \_\_\_\_\_

NOTES: \_\_\_\_\_

APPROVAL: \_\_\_\_\_

*In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.*

| Optional Accessories   |                                                                                                             |                                                                                     |
|------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <a href="#">51299C</a> | Elkay WaterSentry <sup>®</sup> Replacement Filter (Coolers + Fountains)<br><a href="#">Spec Sheet (PDF)</a> |  |
| <a href="#">MF200</a>  | Elkay Mounting Frame for Bi-level In-wall Refrigerated Coolers<br><a href="#">Spec Sheet (PDF)</a>          |  |
| <a href="#">LKAPR1</a> | Elkay Cane Apron for SwirlFlo Gray<br><a href="#">Spec Sheet (PDF)</a>                                      |  |
| <a href="#">97446C</a> | Bubbler Kit Vandal-Resistant<br><a href="#">Spec Sheet (PDF)</a>                                            |  |

*In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit [elkay.com](http://elkay.com) for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.*

