



SYMMONS® Temptrol®

the smart choice™

PRESSURE BALANCING SHOWER VALVE BODY SPECIFICATION SUBMITTAL

MODEL NUMBERS

- ☐ **261XBODY**
Pressure Balancing shower valve body
- ☐ **161XBODY**
Pressure Balancing shower valve body with pressure testing cap

FEATURE HIGHLIGHTS

- Brass, bronze and stainless steel construction
- Pressure balancing mixing valve to maintain safe shower temperature
- Adjustable stop screw to control maximum hot water temperature to valve
- Integral service stops allow water shut-off for valve servicing
- 3 port valve body in common plane
- Inlets: 1/2" IPS and 1/2" sweat
- Outlet: 1/2" IPS and 1/2" sweat
- Accommodates back to back installations
- Accommodates thin wall installations
- Stringer mounts included

OPTIONS/MODIFICATIONS

- ☐ **-BR** Mounting bracket
- ☐ **-CHKS** Integral check stops for use in installations where a positive shut-off device is used downstream of valve
- ☐ **-RV** Reverse seat for back to back installations

INLET/OUTLET ADAPTERS

- ☐ **-CP** CPVC fittings
- ☐ **-P1** PEX crimp fittings
- ☐ **-P2** PEX expansion fittings
- ☐ **-P3** ProPress fittings

COMPLIANCE

- ASME A112.18.1/CSA B125.1
- ASSE 1016
- Buy American Act Compliant



WARRANTY

Limited Lifetime - to the original end purchaser in consumer installations.

5 Years - for commercial installations.

Refer to www.symmons.com/warranty for complete warranty information.

